

# Product Datasheet

## Fire Rated Mailboxes - FR2



The Fire Rated FR2 is a horizontal type mailbox suitable for front entry / front retrieval and is produced to meet the mailbox Fire Rating Standards BS476 (Part 6 & 7, and Part 22). The Fire Rated 2 mailbox is manufactured using zintec steel and comes complete with a range of features that ensures both the mailbox and project location is compliant with Fire Rated Standards. Fire Rated features include a lock cover, intumescent aperture seal and an inward sprung hinge flap. Mailboxes can be finished in any colour from the our standard RAL colour range to suit project branding.



**A horizontal Fire Rated mailbox that includes multiple improved features and restricts the spread of fire for up to one hour only**

- Dimensions (mm): 276W x 125H x 360D
- Aperture Dimensions (mm): 235W x 26H
- Manufactured using zintec steel and finished with polyester powder coating to a choice of colours from the standard range of colours that meet the London Underground surface spread of flame specification BS476 Part 6 & 7
- Conforms to Fire Rating standards BS476 Part 22:1987 Clause 8 and EN13724 guidelines
- Strategically placed intumescent closures with special fire rated locking mechanism
- Suitable for both domestic and commercial use
- Configured to meet project requirements



### INSTALLATION OPTIONS (installation options cannot be applied to all models)

| Freestanding (Support Legs) | Freestanding (Support Table) | Recessed or Wall Mounted | Through The Wall | With Door Entry System | Bespoke Arrangement |
|-----------------------------|------------------------------|--------------------------|------------------|------------------------|---------------------|
|                             |                              |                          |                  |                        |                     |