



COLOURS

AG Paving Blocks

Country Cobble®

traditional rumbled paving blocks

DEPTHS



50 | 60 | 80
Millimetres

FINISH

Rm

Rumbled

200 x 150mm | 150 x 150mm | 150 x 100mm

Country Cobble®
colours

COLOURS

For 'Stock Information' on colours availability - see page 3.



CASHEL



KILLYLEAGH



CORRIB



BURREN



SLATE



Frost Resistant



Pedestrian Use



Light Traffic



Heavy Traffic
80mm only



Abrasion Resistant





Country Cobble®

traditional rumbled paving blocks

DEPTHS




50 | 60 | 80
Millimetres

FINISH

Rm

Rumbled



STANDARDS + PERFORMANCE

Product Type	Traditional rumbled paving blocks
Manufactured to	hEN 1338:2003
Through Mix Efflorescence	Country Cobble® features an all-through mix State-of-the-art factory controlled vapour curing significantly reduces this naturally occurring chemical reaction
Tensile Splitting Strength	>3.6Mpa. This applies to all sizes and depths For specific force performance on a given size or depth please contact our Technical Specification Department
Installed to	BS 7533-4:2006
NBS Plus	Q24 110

SUSTAINABILITY

Energy Use	100% renewable
Water Used	100% recycled water
Recyclable	100% of this product can be recycled
Manufacturing	Produced in the UK using responsibly sourced materials
Non-Primary Materials	61 – 70%
Waste Wood + Plastic	100% recycled
BREEAM	50 – 60mm: A Rating – according to the Green Guide to Specification 4th edition 2009. A+ Rating can be achieved when used in conjunction with a prepared recycled sub-base
	80mm: B Rating – according to the Green Guide to Specification 4th edition 2009. A Rating can be achieved when used in conjunction with a prepared recycled sub-base

AG RECOMMENDATIONS

Close Jointing

AG recommends a close joint of between 2mm - 5mm as per BS 7533 to cater for product alignment (butt jointing should be avoided).

Jointing Sand

AG recommends that silver and slate coloured products are jointed with AG's Granite Sand.

Colour blending

AG recommends that products are blended from 3 packs from alternate sides using full vertical sections.

Please contact our Technical Specification Department for further details.

ADVICE + GUIDANCE

For advice and guidance on ordering, installation, good site practice, etc. visit our website:
www.ag.uk.com/advice+guidance

For maintenance guidance and health and safety advice visit our website:
www.ag.uk.com/maintenance

EDGES

Country Cobble® Supplied with a rumbled edge as standard.



Rumbled

SPACER NIBS

No formed spacer which allows for close jointing.

FINISHES

Country Cobble® is made with a colourfast, all-through mix of UV resistant pigments for vibrant, durable, lasting colours. It is rumbled with traditional methods to honour the authentic old cobble effect.



Frost Resistant



Pedestrian Use



Light Traffic



Heavy Traffic 80mm only



Abrasion Resistant

SPECIFICATION REFERENCE: NBS PLUS: Q24 110 SLAB/BRICK/SETT/COBBLE PAVINGS: 31, 315; hEN: 1338:2003





Country Cobble®

traditional rumbled paving blocks

DEPTHS




50 | 60 | 80
Millimetres

FINISH



Rm

Rumbled



STOCK INFORMATION

Standard Product Depth	Size (mm)	In Stock	Available Colours	m ² per pack	Units per m ²	Units per pack	Unit weight (kg)	Weight per pack (t)	Packs per 8 wheeler	Packs per unit lorry
50mm	200 x 150	Yes	Cashel / Killyleagh / Slate / Burren / Corrib	12	33	400	3.2	1.32	14	IRE 20 / GB 21
	150 x 150	Yes	Cashel / Killyleagh / Slate / Burren	11.25	44	500	2.5	1.2	14	IRE 20 / GB 23
	100 x 150	Yes	Cashel / Killyleagh / Slate	12	66	800	1.6	1.32	14	IRE 20 / GB 21
60mm	200 x 150	Yes	Cashel / Slate	9.6	33.3	320	4	1.28	14	IRE 20 / GB 21
		MTO	Killyleagh / Burren							
80mm	200 x 150	Yes	Cashel / Slate	7.2	33.3	240	5.3	1.26	14	IRE 20 / GB 22
		MTO	Killyleagh / Burren							

NB. Items 'in stock' are supplied as patio packs and MTO items are supplied in full packs.

MTO: Made To Order (minimum order quantities: 250m² per colour / size. Orders below these quantities should be priced on application).

SETTS

Country Cobble® Sets are available - see the Sets data sheet for more information.



MANUFACTURING

Country Cobble® is manufactured from high grade locally sourced aggregates. Its unique three colour blends are obtained by using the latest computerised mixing systems. Rumbled finish. PLANT OF MANUFACTURE: Made at our Fivemiletown production plant.

CERTIFICATION

ISO 9001
ISO 14001
ISO 45001
CE Marking

Quality Management.
Environmental Management.
Occupational Health and Safety Management.
Download our Declaration of Performance (DOP) data at:
www.ag.uk.com/resources



Frost Resistant



Pedestrian Use



Light Traffic



Heavy Traffic
80mm only



Abrasion Resistant