

Rosemount

smooth flagstones

DEPTHS



40
Millimetres

FINISH

Smo

Smooth



400 x
400mm



600 x
400mm

Rosemount
colours

COLOURS

For 'Stock Information' on colours availability - see page 3.



SILVER



SLATE



BUFF



Frost
Resistant



Pedestrian
Use



Abrasion
Resistant

Rosemount

smooth flagstones

DEPTHS

40
Millimetres

FINISH

Smo

Smooth

400 x
400mm600 x
400mmRosemount
technical information

STANDARDS + PERFORMANCE

Product Type	Functional flagstones with a smooth finish
Manufactured to	hEN 1339:2003
Surface Layer	Durable and hard wearing with a minimum surface layer of 8mm
Granite / Quartz Content	Not less than 50% natural granite and quartz aggregate in surface layer
Efflorescence	State-of-the-art factory controlled vapour curing significantly reduces this naturally occurring chemical reaction
Bending Strength	>3.5Mpa Class 1
Slip / Skid Resistance	(USRV) >75 extremely low potential for slip. Specific slip / skid resistance test results are available on request from our Technical Specification Department
Installed to	BS 7533-4:2006
NBS Plus	Q25 315

SUSTAINABILITY

Energy Use	100% renewable
Water Used	100% recycled water
Recyclable	100% of this product can be recycled
Manufacturing	Produced in the UK using responsibly sourced materials
Non-Primary Materials	52 – 60% (surface layer)
Waste Wood + Plastic	100% recycled
BREEAM	A Rating – according to the Green Guide to Specification 4th edition 2009. A+ Rating can be achieved when used in conjunction with a prepared recycled sub-base

AG RECOMMENDATIONS

Close Jointing

AG recommends a close joint of between 2mm - 5mm as per BS 7533 to cater for product alignment (butt jointing should be avoided).

Jointing Sand

AG recommends that silver and slate coloured products are jointed with AG's Granite Sand.

Colour blending

AG recommends that products are blended from 3 packs from alternate sides using full vertical sections.

Please contact our Technical Specification Department for further details.


ADVICE + GUIDANCE

For advice and guidance on ordering, installation, good site practice, etc. visit our website:
www.ag.uk.com/advice+guidance

For maintenance guidance and health and safety advice visit our website:
www.ag.uk.com/maintenance

EDGES

Rosemount is supplied with a nominal 5mm wide x 3mm deep straight chamfer edge as standard.



Straight Chamfer

SPACER NIBS

No formed spacer.

FINISHES

Smooth finish.

Frost
ResistantPedestrian
UseAbrasion
Resistant

SPECIFICATION REFERENCE: NBS PLUS: Q25 SLAB/BRICK/SETT/COBBLE PAVINGS: 31, 315; hEN: 1339:2003

Rosemount

smooth flagstones


DEPTHS

40
Millimetres

FINISH

Smo

Smooth

400 x
400mm600 x
400mmRosemount
Stock InformationFrost
ResistantPedestrian
UseAbrasion
Resistant

STOCK INFORMATION

Standard product depth	Size (mm)	In Stock	Available Colours	m ² per pack	Units per m ²	Units per pack	Unit weight (kg)	Weight per pack (t)	Packs per 8 wheeler	Packs per unit lorry
40mm	600 x 600	MTO	Silver / Slate / Buff – coming soon in 2023							
	400 x 400	Yes	Silver / Slate / Buff	14.72	6.25	92	16.09	1.41	10	IRE 15 / GB 19

Information for a specific colour / depth is available on request from our Technical Specification Department.

MANUFACTURING

Rosemount flags are manufactured from quality aggregates – including granite and quartz. PLANT OF MANUFACTURE: Made at our Ballygawley production plant.

CERTIFICATION

ISO 9001
ISO 14001
ISO 45001
CE Marking

Quality Management.
Environmental Management.
Occupational Health and Safety Management.
Download our Declaration of Performance (DOP) data at: www.ag.uk.com/resources